



POOLS | HOT TUBS | SAUNAS | PATIO

Making Water Wonderful since 1962

FROG @EASE

Water Care Instructions

(FROG low chlorine)

Start-Up Procedures

1. To fill up the spa: Remove one of the filter cartridges and place hose inside of the hole and fill tub to cover the highest set of jets.
2. Turn the power on to start circulating the water. Keep cover closed. Allow water to heat up to at least 80 degrees before adding any chemicals.
3. Add 1 oz. of Pettis Spa Metal & Scale Control. Let this circulate for 30 minutes.
4. Add the @Ease Jump-Start packet into the spa water and wait 20 minutes.
300 gallons or less = ½ packet 350 to 600 gallons – 1 full packet
5. Snap together the Blue Mineral half of the ball and a Silver Chlorine cartridge.

Set dial according to the chart below.

6. Add 12-16 oz. of Calcium Hardness Increaser. Only add 2 oz. every 20 to 30 minutes. Water with appropriate calcium levels foams less, sparkles better and the water is less aggressive towards metals and plastics.
7. Wait at least 24 hours to bring in a water sample to be tested for any chemical adjustments.

Setting # on FROG @EASE Silver Cartridge

Appropriate Levels

Measurement Conversions

Settings Chart	
Gallons	Setting #
200-299	1
300-450	2
451-550	3
551-600	4

- Chlorine: 0.5-1 ppm
- pH: 7.2-7.8
- Alkalinity: 80-120ppm
- Calcium Hardness: 150-250
- ½ oz = 1 tablespoon
- 1oz = 2 tablespoons
- 2oz = ¼ cup
- 8oz = 1 cup

Helpful Hints:

- Always run the spa jets when adding chemicals.
- Leave spa cover open or off for 20-30 minutes after adding monthly shock– impurities need to off-gas.
- Wash the area above the waterline with chlorinated spa water or surface cleaner weekly.

1186 Manitou Rd
Hilton, NY 14468
585-392-7711

www.pettispools.com

825 Fairport Rd
East Rochester, NY 14445
585-383-0700



POOLS | HOT TUBS | SAUNAS | PATIO
Making Water Wonderful since 1962

FROG @EASE

Water Care Instructions

(FROG low chlorine)

When Necessary:

Replace the “Smart-Chlor” Cartridge – the silver half of the @Ease ball whenever the silver side is on top. This should every 2-3 weeks.

Remember to set the arrow on the silver half to the appropriate number based on the hot tub gallonage. (Chart on other side)

Weekly Maintenance Procedures

1. Test water with test strips and adjust levels as necessary. If you are unsure, bring in 4-6 oz of spa water to Pettis for a computerized water test.

NOTE: *only use FROG @Ease Test strips. Regular test strips cannot test for Smart-Chlor*

2. If using well water: Add 1 oz. of Spa Metal & Scale Protector. Circulate for 30 minutes before adding your normal weekly chemicals as directed above.
3. Wash the area above the waterline with chlorinated spa water or surface cleaner.
4. Make sure the water level is up and covering the highest jet. Topping up the water level is normal.

Every two weeks:

1. Rinse filter cartridge to remove any debris. Inspect for discoloration, which means the cartridge needs to be chemically cleaned or changed.

Monthly:

1. Add 1-2 oz of Non-Chlorine Spa Shock.
2. Chemically clean or change out the filter cartridge.
3. Bring in a water sample to Pettis Pools for a computerized water test.

Reminders:

- Always leave spa cover open after adding chlorine.
- Always close air-injector knobs when not using the spa.
- Spa water needs to be drained and refilled every 4 months.
- Clean the underside of the spa cover occasionally with a bleach water solution to prevent odors.

1186 Manitou Rd
Hilton, NY 14468
585-392-7711

www.pettispools.com

825 Fairport Rd
East Rochester, NY 14445
585-383-0700