



POOLS | HOT TUBS | SAUNAS | PATIO

Making Water Wonderful since 1962

Water Care Instructions for Brilliance Bromine

Start-Up Procedures

1. To fill up the spa: Remove one of the filter cartridges and place hose inside of the hole and fill tub to cover the highest set of jets.
2. Turn the power on to start circulating the water. Allow water to heat up to at least 80 degrees before adding any chemicals
3. Add 1 oz. of Brilliance Spa Metal & Scale Control. Let this circulate for 30 minutes
4. Add one 2 oz. Brilliance Start-Up packet into the spa water and wait 20 minutes
5. Add 3-4 tablets of Brilliance Spas Oxidizing Tablets into the spa water and allow the water to circulate with the cover off for 15 minutes (See Chart Below)
6. Fill the Brilliance floater with 4 tablets of Brilliance Bromo Tabs and open the floater to a medium range (between 4-6)
7. Add 8 oz. of Calcium Hardness Increaser. Only add 2 oz. every 20 to 30 minutes.
8. Wait approximately 24 hours and bring in a water sample to be tested for any chemical adjustments.

Start-Up Oxidizer Tablets

100 Gallons:	1 tab
200 Gallons:	3 tabs
300 Gallons:	4 tabs
400 Gallons:	5 tabs
500 Gallons	6 tabs

Measurement Conversions

- $\frac{1}{2}$ oz = 1 tablespoon
- 1oz = 2 tablespoons
- 4oz = $\frac{1}{2}$ cup
- 8oz = 1 cup

Helpful Hints:

- Always run the spa jets when adding chemicals.
- Leave covers open for 20-30 minutes after adding chlorine or non-chlorine shock – the impurities need to off-gas
- Wash the area above the waterline with spa water weekly after adding Oxi-Tabs to clean this surface.



POOLS | HOT TUBS | SAUNAS | PATIO

Making Water Wonderful since 1962

Water Care Instructions for Brilliance Bromine

Weekly Maintenance Procedures:

1. Test water with test strips and adjust levels as necessary. If you are unsure, bring in 4-6 oz of spa water to Pettis for a computerized water test.
2. Add 1oz. of Brilliance Spa Metal & Scale Control Let this circulate for 30 minutes before adding your normal weekly chemicals as directed above.
3. Wash the area above the waterline with brominated spa water to clean this surface or use spa surface cleaner.
4. Add 4 Brilliance Oxidizing Tablets - drop into spa water. Circulate for 30 minutes with cover off.

Every two weeks:

1. Rinse filter cartridges to remove any debris. Inspect for discoloration which means the cartridges need to be chemically cleaned.
2. Make sure the water level is up and covering the highest jet. Topping up the water level is a regular occurrence.

Monthly:

1. Chemically clean the filter cartridge(s)
2. Bring in a water sample to Pettis Pools for a computerized water test.

Weekly Oxidizer Tablets

100 Gallons:	1 tab
200 Gallons:	3 tabs
300 Gallons:	4 tabs
400 Gallons:	5 tabs
500 Gallons	6 tabs

Appropriate Levels

- Bromine: 3-5 ppm
- pH: 7.2-7.8
- Alkalinity: 80-120ppm
- Calcium: 200-500

Reminders:

- Always leave spa cover open after adding Oxi-Tabs shock or granular bromine
- Always close air-injector knobs when not using the spa.
- Spa water needs to be drained and refilled every 4 months.
- Clean the underside of the spa cover occasionally with bleach water to prevent odors